

CLEANING BRUSHES

For clean surface tube end before soldering.

- Stainless Steel bristles;
- Hand use.



TCB-10

Model	Description
TCB- 4	Cleaning brush for copper and brass 1/4" (Ø 6,35 mm.) OD tubing.
TCB- 6	3/8" (Ø 9,52 mm.) OD.
TCB- 8	1/2" (Ø 12,70 mm.) OD.
TCB-10	5/8" (Ø 15,88 mm.) OD.
TCB-12	3/4" (Ø 19,05 mm.) OD.
TCB-14	7/8" (Ø 22,22 mm.) OD.
TCB-16	1" (Ø 25,40 mm.) OD.
TCB-18	1-1/8" (Ø 28,58 mm.) OD.

2-in-1 COPPER TUBE / FITTING CLEANING BRUSH

One end cleans the fitting, the other cleans the tube.

- A combination tool that fits your hand comfortably and cleans perfectly and quickly;
- Stainless Steel bristles;
- To clean turn the brush in a CLOCKWISE motion.



TC21-1214

Model	Description
TC21- 810	2-in-1 copper and brass tube cleaning brush for 5/8" (Ø 15,88 mm.) ID/OD. Carbon steel brushes.
TC21-1214	7/8" (Ø 22,22 mm.) ID/OD.

FOUR-IN-ONE BRUSH

- Stainless Steel bristles;
- To clean turn the brush in a CLOCKWISE motion.



TC21- 812

Model	Description
TC21- 812	Four-in-one Brush for cleaning 1/2" (Ø 12,70 mm.) and 3/4" (Ø 19,05 mm.) ID/OD tubing.
TC21-1014	5/8" (Ø 15,88 mm.) and 7/8" (Ø 22,22 mm.) ID/OD.

Spare Parts

TC21X 812	Stainless Steel brushes 1/2" (Ø 12,70 mm.) and 3/4" (Ø 19,05 mm.) ID/OD tubing.
TC21X1014	5/8" (Ø 15,88 mm.) and 7/8" (Ø 22,22 mm.) ID/OD.

COPPER FITTING BRUSHES

For cleaning, scoring and preparing copper fittings and tubes for soldering.

- Spring tempered stainless steel wire bristles. Precision trimmed to ensure maximum contact of the bristle ends and cutting edges;
- Interlaced double spiral construction;
- Solid plastic hand-fitting handle with hole for hanging;
- S



TC2-__ Single Spiral/single Stem (2 wire) Brush bristles are twisted between two stem wires with a single wire on each side.



TC2- 8

Model	Description
TC2- 4	Stainless Steel single spiral / single stem Fitting Brush for 1/4" (Ø 6,35 mm.) OD. Fill 0,005" (Ø 0,127 mm.) Dia.
TC2- 6	3/8" (Ø 9,52 mm.) OD. Fill 0,005" (Ø 0,127 mm.) Dia.
TC2- 8	1/2" (Ø 12,70 mm.) OD. Fill 0,005" (Ø 0,127 mm.) Dia.
TC2-10	5/8" (Ø 15,88 mm.) OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC2-12	3/4" (Ø 19,05 mm.) OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC2-14	7/8" (Ø 22,22 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC2-16	1" (Ø 25,40 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC2-18	1-1/8" (Ø 28,58 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC2-22	1-3/8" (Ø 34,92 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC2-24	1-1/2" (Ø 38,10 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC2-26	1-5/8" (Ø 41,28 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC2-34	2-1/8" (Ø 53,98 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.

TC4-__ Single Spiral/Double Stem (4 wire) Brush bristles are twisted between two stem wires with a single wire on each side.



TC4-12

TC4- 6	Stainless Steel single spiral / double stem Fitting Brush for Ø 3/8" OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC4- 8	1/2" (Ø 12,70 mm.) OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC4-10	5/8" (Ø 15,88 mm.) OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC4-12	3/4" (Ø 19,05 mm.) OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC4-14	7/8" (Ø 22,22 mm.) OD. Fill 0,006" (Ø 0,152 mm.) Dia.
TC4-16	1" (Ø 25,40 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC4-18	1-1/8" (Ø 28,58 mm.) OD. Fill 0,008" (Ø 0,203 mm.) Dia.
TC4-22	1-3/8" (Ø 34,92 mm.) OD. Fill 0,009" (Ø 0,229 mm.) Dia.
TC4-24	1-1/2" (Ø 38,10 mm.) OD. Fill 0,009" (Ø 0,229 mm.) Dia.
TC4-26	1-5/8" (Ø 41,28 mm.) OD. Fill 0,009" (Ø 0,229 mm.) Dia.
TC4-34	2-1/8" (Ø 53,98 mm.) OD. Fill 0,009" (Ø 0,229 mm.) Dia.

POWER FITTING BRUSH

1/4" (6,35 mm.) hex shank brushes with Stainless Steel bristles clean fittings fast. Hex locks into all standard and quick lock type chucks for easy change over.

- 2,000 RPM without Hex chuck;
- Stainless Steel - Single Spiral/Single Stem.



Single Spiral/single Stem (2 wire) Brush bristles are twisted between two stem wires with a single wire on each side.



PFB-10

Model	Description
PFB- 4	Stainless Steel single spiral / single stem Power Fitting Brush for 1/4" (6,35 mm.) I.D. - 3/8" (Ø 9,52 mm.) OD. Fill. 0,005" (Ø 0,127 mm.) Dia.
PFB- 6	3/8" (Ø 9,52 mm.) I.D. - 1/2" (Ø 12,70 mm.) OD. Fill. 0,005" (Ø 0,127 mm.) Dia.
PFB- 8	1/2" (Ø 12,70 mm.) I.D. - 5/8" (Ø 15,88 mm.) OD. Fill. 0,006" (Ø 0,152 mm.) Dia.
PFB-10	5/8" (Ø 15,88 mm.) I.D. - 3/4" (Ø 19,05 mm.) OD. Fill. 0,006" (Ø 0,152 mm.) Dia.
PFB-12	3/4" (Ø 19,05 mm.) I.D. - 7/8" (Ø 22,22 mm.) OD. Fill. 0,008" (Ø 0,203 mm.) Dia.