

PREMIUM VACUUM PUMP OIL

ENALT offers industrial non-detergent based Vacuum Pump Oil. It is highly refined using a 3 Step hydroprocess method which ensures a cleaner operating environment to allow the deepest vacuum possible.

Viscosity : SuS 250 - ISO 460 at 37,8° C. (100° F.);

Vapor Pressure : <0,01 mmHg @ 37,8° C. (100° F.);

Boiling Point : >315° C. (>600° F.);

Solubility : Soluble in hydrocarbons, insoluble in water;

Specific Gravity : 0,85 ÷ 0,87 at 15,6° C. (60° F.);

The best results may be obtained from a mechanical high vacuum pump only when oil of the lowest Vapor Pressure is used. One of the important functions of the oil is to absorb unwanted vapors passing through the pump. Therefore, oil should be changed frequently for best results.

Pump Warranty may be voided if oil other than that specified by the manufacturer is used.



DVO- 1

DVO-12

DVO-24

Model	Description
DVO- 1	Premium Vacuum Pump Oil. 0,47 I. (1 Pint) Bottle.
DVO-12	Premium Vacuum Pump Oil. 0,94 I. (Quart) Bottle.
DVO-24	Premium Vacuum Pump Oil. 3,78 I. (1 Gal.) Bottle.