

CLEAR POLYETHYLENE TUBE

For Evaporative Coolers, Vending Machine, Water Cooler, Refrigeration drain tubes, Condensate Removal Pump Split System EC-400 Model discharge line.

- It is clear, flexible, easy to clean, abrasion resistant and non-contaminating;
- Non-toxic, Tasteless, odorless;
- F.D.A. Approved.

Working Pressure : 10,4 Bar (150 Psi) - 21,1° C. (70° F.).



PET-104

Model	Description
PET-104	Clear Polyethylene Tube. 0.17" (4,3 mm.) I.D. / 0.25" (6,3 mm.) O.D. Roll 100' (30,4 m.) in Dispenser Pack.

CLEAR VINYL TUBING

Applications include: Evaporative Coolers, Water lines to machinery, AC&R Air Conditioning & Refrigeration condensate drains, condensate pump discharge lines and Humidifier overflows, clean the interior lines of evaporator and condenser with CF-20 flush after a compressor burnout...

- It is clear, flexible, easy to clean, abrasion resistant and non-contaminating;
- Non-toxic;
- Replacement of copper tubing.

Temperature range : -5,0° ÷ 65,5° C. (25° F. to 150° F.);

NOTE : For Hose Clamps see Page 16d "Components" Section.



CVT- 6

Model	Description
CVT- 3	Clear Vinyl Tube 4,76 mm. (3/16") I.D. Working Pressure 1,45 Bar (21 Psi). Roll 30,4 m. (100') in Dispenser Pack.
CVT- 4	1/4" (6,35 mm.) I.D. 2,20 Bar (32 Psi) - 30,4 m. (100').
CVT- 6	3/8" (9,52 mm.) I.D. 1,87 Bar (27 Psi) - 30,4 m. (100').
CVT- 8	1/2" (12,7 mm.) I.D. 1,66 Bar (24 Psi) - 30,4 m. (100').
CVT-10	5/8" (15,8 mm.) I.D. 1,46 Bar (21 Psi) - 30,4 m. (100').
CVT-12	3/4" (19,0 mm.) I.D. 1,32 Bar (19 Psi) - 30,4 m. (100').
CVT-14	7/8" (22,2 mm.) I.D. 1,11 Bar (16 Psi) - 15,2 m. (50').
CVT-16	1" (25,4 mm.) I.D. 1,04 Bar (15 Psi) - 15,2 m. (50').

PLASTIC A/C SECONDARY CONDENSATE DRAIN PANS - For Use in Horizontal Applications

For Heat Pump Condensing Units, Horizontal Fan-coils, High Efficiency Horizontal Furnaces...

- Made of high-impact ABS plastic;
- Rolled edges for durability;
- Ribbed bottoms for rigidity;
- Reinforced corners for strength;
- 3/4" PVC fittings attached to each pan;
- No seams, rust or leakage;
- Does not put out toxic smoke;
- Complies with Southern Building Code No. 94167 U.S.A.



SCDP-1246S

Model	Description
SCDP-1246L	Plastic A/C Secondary Condensate Drain Pan. Drain Line Outlets in Long Side . Bottom Dimensions 12" x 46" (305 x 1.168 mm.).
SCDP-1838L	18" x 38" (458 x 965 mm.).
SCDP-1846L	18" x 46" (458 x 1.168 mm.).
SCDP-2424L	24" x 24" (610 x 610 mm.).
SCDP-2626L	26" x 26" (660 x 660 mm.).
SCDP-2739L	27" x 39" (686 x 990 mm.).
SCDP-2748L	27" x 48" (686 x 1.220 mm.).
SCDP-2763L	27" x 63" (686 x 1.600 mm.).
SCDP-3030L	30" x 30" (762 x 762 mm.).
SCDP-3050L	30" x 50" (762 x 1.270 mm.).
SCDP-3060L	30" x 60" (762 x 1.525 mm.).
SCDP-3263L	32" x 63" (813 x 1.600 mm.).
SCDP-3636L	36" x 36" (915 x 915 mm.).
SCDP-3660L	36" x 60" (915 x 1.525 mm.).
SCDP-1246S	Plastic A/C Secondary Condensate Drain Pan. Drain Line Outlets in Short Side . Bottom Dimensions 12" x 46" (305 x 1.168 mm.).
SCDP-1838S	18" x 38" (458 x 965 mm.).
SCDP-1846S	18" x 46" (458 x 1.168 mm.).
SCDP-2748S	27" x 48" (686 x 1.220 mm.).
SCDP-2763S	27" x 63" (686 x 1.600 mm.).
SCDP-3050S	30" x 50" (762 x 1.270 mm.).
SCDP-3060S	30" x 60" (762 x 1.525 mm.).
SCDP-3263S	32" x 63" (813 x 1.600 mm.).
SCDP-3660S	36" x 60" (915 x 1.525 mm.).